



Torque

Maximum Starting Torque Values For ABEC 7P Bearings

NHBB BASIC SIZE	TEST LOAD (THRUST) GRAMS	MAXIMUM STARTING TORQUE MILLIGRAM – MILLIMETERS		
		RADIAL PLAY		
		TIGHT FIT .0001" – .0003"	NORMAL FIT .0002" – .0005"	LOOSE FIT .0005" – .0008"
SSRI-2	75	1,800	1,500	1,400
SSRI-2 1/2	75	1,800	1,500	1,400
SSRI-3	75	1,800	1,500	1,400
SSRI-4	75	1,800	1,500	1,400
SSRI-5	75	1,800	1,500	1,400
SSRI-418	75	1,800	1,500	1,400
SSRI-518	75	1,800	1,500	1,400
SSRI-618	75	2,000	1,600	1,500
SSR-2	400	5,000	4,500	4,200
SSR-2A	400	5,000	4,500	4,200
SSRI-5532	75	1,800	1,500	1,400
SSRI-5632	75	1,800	1,500	1,400
SSRI-6632	75	2,000	1,600	1,500
SSR-3	400	6,500	5,500	5,000
SSRI-614	75	1,800	1,500	1,400
SSRI-814	400	6,000	5,200	4,800
SSR-4	400	7,000	6,000	5,500
SSRI-1214	400	8,000	7,000	6,500
SSRI-1438	400	11,000	9,500	9,000